

XP-002241109

1000000000  
10/500280  
DT04 R PCT/PTO 28 JUN 2004

AN - 1988-298406 [42]  
AP - SU19864079124 19860505  
CPY - SASO-R  
DC - J01  
FS - CPI  
IC - B01D45/12  
IN - NUZHDIN Y U I  
MC - J01-G02  
PA - (SASO-R) SARAT SOYUZGAZAUTOM  
PN - SU1386248 A 19880407 DW198842 003pp  
PR - SU19864079124 19860505  
XA - C1988-132597  
XIC - B01D-045/12  
AB - SU1386248 Cylindrical vessel (1) has inside it sepg. tray (2) overflow pipe (3) and transverse partition (4). Pipes (5, 6, 7) are provided for delivery, removal of gas and removal of liq. Contact tubes (8) have slots (9) in bottom ends and are tightly fitted in the tray (2) and partition (4). The latter has attached conical shell (10) with heater (11) fitted at the bottom. The partition (4) has slots through on its periphery, with tangentially directed folds.  
- USE/ADVANTAGE - In petrochemical, gas and other industries, for sepn. of liq. droplets from natural gas at high pressure using cooling effect of expanded gas, to increase productivity and efficiency.(1/4)  
IW - GAS SEPARATE INVERT CONICAL SHELL BASE ATTACH HORIZONTAL PARTITION LOCATE BELOW GAS INLET  
IKW - GAS SEPARATE INVERT CONICAL SHELL BASE ATTACH HORIZONTAL PARTITION LOCATE BELOW GAS INLET  
INW - NUZHDIN Y U I  
NC - 001  
OPD - 1986-05-05  
ORD - 1988-04-07  
PAW - (SASO-R) SARAT SOYUZGAZAUTOM  
TI - Gas separator - has inside inverted conical shell with base attached to horizontal partition located below gas inlet